



Model number	RF ONU	
Picture		
Eth port quantity	4	
Eth bandwidth	100Mbps	
PON port type	SC	
RF output port quantity	1	
CATV input port quantity	1	
Optical power of CATV input port	+2.0dBm~-22dBm	
Transmitted power of RF output port	82-90.4dBμV	
Feature	Wavelength	PON: TX: 1310 nm; RX: 1490 nm CATV: 1550nm
	Fiber	Single fiber
	Splitting ratio	1:64
Dimension	165mm*115mm*30mm	
Weight	0.3KG	
Power supply	DC-12V	
Power consumption	5W	
Work temperature	-30 °C ~ +50 °C	
Store temperature	-40 °C ~ +75 °C	
Relative humidity	5% ~90% No condensation	

Model number	RF ONU with built-in WDM	
Picture		
Eth port quantity	4	
Eth bandwidth	100Mbps	
PON port type	SC, built-in WDM module	
RF output port quantity	1	
Optical power of CATV input port	+2.0dBm~-22dBm	
Transmitted power of	82-90.4dB μ V	

<b>RF output port</b>		
<b>Feature</b>	<b>Wavelength</b>	PON: TX: 1310 nm; RX: 1490 nm CATV: 1550nm
	<b>Fiber</b>	Single fiber
	<b>Splitting ratio</b>	1:64
<b>Dimension</b>		165mm*115mm*30mm
<b>Weight</b>		0.3KG
<b>Power supply</b>		DC-12V
<b>Power consumption</b>		5W
<b>Work temperature</b>		-30 °C ~ +50 °C
<b>Store temperature</b>		- 40 °C ~ +75 °C
<b>Relative humidity</b>		5% ~90% No condensation

<b>Model number</b>		<b>WIFI ONU</b>
<b>Picture</b>		Waiting for update
<b>Eth port quantity</b>		4
<b>Eth bandwidth</b>		100Mbps
<b>PON port type</b>		SC
<b>WIFI</b>		1
<b>Feature</b>	<b>Wavelength</b>	PON: TX: 1310 nm; RX: 1490 nm
	<b>Fiber</b>	Single fiber
	<b>Splitting ratio</b>	1:64
<b>Dimension</b>		165mm*115mm*30mm
<b>Weight</b>		0.3KG
<b>Power supply</b>		DC-12V
<b>Power consumption</b>		5W
<b>Work temperature</b>		-30 °C ~ +50 °C
<b>Store temperature</b>		- 40 °C ~ +75 °C
<b>Relative humidity</b>		5% ~90% No condensation